



## FortiVoice™ 200D/200D-T

Voice Appliance for Enterprise Networks



The FortiVoice 200-series IP PBX voice solution gives you total call control and sophisticated communication features for excellent customer service and efficient employee collaboration. Powerful, affordable and simple, the FortiVoice 200D and 200D-T systems deliver the features and value of the proven FortiVoice product line to offices with up to 2000 phone users. FortiVoice phone systems include everything you need to handle calls professionally, control communication costs and stay connected everywhere.

#### **Built-in fundamentals**

FortiVoice 200 systems include all the fundamentals of enterprise-class voice communications, with no additional licenses to buy or cards to install. Auto attendants, auto provisioning, line/extension appearance, ring groups, phone profile, call queue, call barge, multibranch integration and much more are built-in. FortiVoice systems are easy to purchase, easy to install and easy to manage, so you save the headaches that come with most enterprise phone systems.

#### **Key Features & Benefits**

| no, routares a zeneme           |  |  |  |
|---------------------------------|--|--|--|
| Digital lines                   | FortiVoice 200D-T supports both PRI (T1/E1/R2) digital lines and traditional analog lines.   |  |  |
| Multibranch networking          | Connects multiple locations, around the block or across the country with no long-distance charges. Directory synchronization among offices.                  |  |  |
| Rich call features              | Line/extension appearance, call queue, call barge, phone profile, ring group, call recording, dialplan fall back, individual/group voicemail, and much more. |  |  |
| Flexibility                     | More call scheduling options, flexible number management, re-assignable extensions, and caller ID modification.  |  |  |
| Ease of configuration           | Visualized auto attendant configuration, built-in DHCP server, phone auto provisioning and web-based management Ul/user web portal.                          |  |  |
| Comprehensive system monitoring | Real-time call status monitoring, call statistics, call logs, and call reports, and network traffic capture.   |  |  |

# The network voice solution from the network security experts

- No licensing; built-in features, including auto attendants, music on hold, remote extensions and much more
- Web-based management and user interfaces
- Password policy enforcement and audit
- Real-time call status monitoring
- · Call recording
- Line/extension appearance
- · Call queue
- Call barge
- Auto provisioning
- Dialplan fallback

FORTIVOICE AWARDS











#### User appeal

Your people will like it too. In addition to working with the userfriendly series of FortiFones, the FortiVoice personal web portal lets your staff view their call logs, configure and manage their own messaging and access other features. Your employees get control over their phones, and your IT staff get a break from having to configure every little change.

#### Virtually available

FortiVoice-VM is a virtual IP-PBX that delivers all of the features of FortiVoice 200-series systems without the hardware. It's the most economical way to get FortiVoice if you're already running your own servers. And if you're a service provider who wants to add hosted solutions to your offerings, FortiVoice-VM is perfect for you. With simple licensing, unprecedented pricing and instant deployment, FortiVoice-VM is better than hardware. Supports up to 250 IP extensions with up to 50 concurrent VoIP calls.

#### **FEATURES**

| Automatic phone provisioning |
|------------------------------|
| Auto attendants              |
| Individual/group voicemail   |
| Remote extensions            |
| Dial-by-name directory       |
| Voicemail to e-mail          |
| Music on hold                |
| Ring groups                  |
| User privileges              |

| Rule-based dialplan                         |
|---|
| Call detail record logging                  |
| Virtual number                              |
| Call conference/bridge                      |
| Mode scheduling                             |
| Call hold/transfer/park/pickup/forward/page |
| 802.1Q VLAN support                         |
| Network traffic capture                     |
| Password policy enforcement and audit       |
|   |

| External extension                  |
|-------------------------------------|
| Personal and system speed dials     |
| Call queue                          |
| Web-based management/user interface |
| Call barge                          |
| Web-based directory lookup          |
| Personal blacklist                  |
| Notification for missed calls       |
| Line/extension appearance           |
|                                     |

| SIP over TLS              |           |
|---------------------------|-----------|
| Phone profile             |           |
| Multibranch networking    |           |
| Follow-me                 |           |
| Caller ID modification    |           |
| Call recording and remote | e storage |
| Real-time call status mor | nitoring  |
| Call report               |           |
| Caller-based direct inwar | d dialing |
|                           |           |

#### **SPECIFICATIONS**

|  | FORTIVOICE 200D      | FORTIVOICE 200D-T    |
|--|----------------------|----------------------|
| MSRP                                   | \$3444               | <sup>\$</sup> 6894   |
| Hardware Specifications                |                      |                      |
| 10/100/1000 Interfaces (Copper, RJ-45) | 4                    | 4                    |
| Traditional Telephone Lines (FXOs)     | 0                    | 4                    |
| Primary Rate Interface (PRI)           | 0                    | 1                    |
| Analog Extension (FXS)                 | 0                    | 1                    |
| Total Hard Drive Capacity              | 1X 1 TB              | 1X 1 TB              |
| Hardware Form Factor                   | Rack Mount (1U)      | Rack Mount (1U)      |
| Dimensions                             |                      |                      |
| Height x Width x Length (in)           | 1.77 x 17.05 x 13.86 | 1.77 x 17.05 x 13.86 |
| Height x Width x Length (mm)           | 45 x 433 352         | 45 x 433 352         |
| Weight                                 | 15.4 lbs (6.98 kg)   | 16 lbs (7.26 kg)     |
| Environment                            |                      |                      |
| Power Required                         | 100-240 V AC         | 100-240 V AC         |
| Power Consumption (Avg.)               | 121 W                | 122.65 W             |
| Heat Dissipation                       | 205 BTU/h            | 210 BTU/h            |
|  | 32-104°F (0-40°C)    | 32-104°F (0-40°C)    |
| Storage Temperature                    | -31–158°F (-35–70°C) | -31–158°F (-35–70°C) |
| Humidity                               | 5–95% non-condensing | 5–95% non-condensing |

All prices USD and include the first year of FortiCare.

FortiVoice 200-series business phone systems are supported for use in the US, Canada, France, Germany, Italy, Spain, the UK, and more. For up-to-date availability information, visit www.fortivoice.com/availability.html.

|                   | FORTIVOICE 200D                         | FORTIVOICE 200D-T | FORTIVOICE-VM* |
|-------------------|---|-------------------|----------------|
| Capacity          |   |                   |                |
| VoIP trunks       | 100                                     | 100               | 50             |
| SIP extensions    | 2000                                    | 2000              | 50             |
| Remote extensions | 100                                     | 100               | 100            |
| Concurrent calls  | 200                                     | 200               | 50             |
| Auto attendants   | 100                                     | 100               | 100            |
| Conferences       | 20                                      | 20                | 20             |
| Voicemail storage | 900 GB                                  | 900 GB            | 900 GB         |
| Codec support     | G.711 μ-law/A-law, G.729a, G.722, G.726 |                   |                |
|                   |   |                   |                |

<sup>\*</sup>Minimum hardware requirement: 1 GB memory, 50 GB disc space. VMWare version ESXi 5.0 or 5.1.

### ORDER INFORMATION

| Product           | SKU         | Description  |
|-------------------|-------------|--|
| FortiVoice-200D   | FVC-200D    | FortiVoice-200D, 4x 10/100/1000 ports, 4 GB RAM, 1x 1 TB storage.                              |
| FortiVoice-200D-T | FS-324B-P0E | FortiVoice-200D-T, 4x 10/100/1000 ports,<br>4x FXO, 1x FXS, 1x PRI, 4 GB RAM, 1x 1 TB storage. |
| FortiVoice-VM     | FVC-VM-BASE | Base license for stackable FortiVoice-VM (includes 50 extensions).                             |
|                   | FVC-VM-25   | License to add 25 extensions to FortiVoice-VM (Maximum 250 in total).                          |



#### GLOBAL HEADQUARTERS EMEA SALES OFFICE

Fortinet Inc. 1090 Kifer Road Sunnyvale, CA 94086 **United States** Tel: +1.408.235.7700

Fax: +1.408.235.7737

120 rue Albert Caquot 06560, Sophia Antipolis, France Tel: +33.4.8987.0510

Fax: +33.4.8987.0501

#### APAC SALES OFFICE

300 Beach Road #20-01 The Concourse Singapore 199555 Tel: +65.6513.3730 Fax: +65.6223.6784

#### LATIN AMERICA SALES OFFICE

Prol. Paseo de la Reforma 115 Int. 702 Col. Lomas de Santa Fe, C.P. 01219 Del. Alvaro Obregón México D.F. Tel: 011-52-(55) 5524-8480

Copyright© 2013 Fortinet, Inc. All rights reserved. Fortinet®, FortiGate®, and FortiGuard®, are registered trademarks of Fortinet, Inc., and other Fortinet names herein may also be trademarks of Fortinet. All other product or company names may be trademarks of their respective owners. Performance metrics contained herein were attained in internal lab tests under ideal conditions, and performance may vary. Network variables, different network environments and other conditions may affect performance results. Nothing herein represents any binding commitment by Fortinet, and Fortinet disclaims all warranties, whether express or implied, except to the extent Fortinet enters a binding written contract, signed by Fortinet's General Counsel, with a purchaser that expressly warrants that the identified product will perform according to the performance metrics herein. For absolute clarity, any such warranty will be limited to performance in the same ideal conditions as in Fortinet's internal lab tests. Fortinet disclaims in full any guarantees. Fortinet reserves the right to change, modify, transfer, or otherwise revise this publication without notice, and the most current version of the publication shall be applicable. Certain Fortinet products are licensed under U.S. Patent No. 5,623,600.

FST-PROD-DS-FV2HR3 FVC-200D 200D-T-DAT-R6-201311